

Express Mail Label
No. EI125463877US

ADM-26A

INTEGRATED SECURITY AND COMMUNICATIONS SYSTEM
WITH SECURE COMMUNICATIONS LINK

Cross Reference to Related Application

[0001] This claims the benefit of copending United
5 States Provisional Patent Application No. 60/188,798,
filed March 13, 2000.

Background of the Invention

[0002] This invention relates to an integrated
security and communications system. In particular,
10 this invention relates to a security system integrated
with a telephone system and/or an Internet connection,
in which various communications features can be
accessed from a keypad of the security system, and
various security system features can be accessed from
15 connected telephone sets.

[0003] Security systems for residential properties
are well known. Such systems at one time were
electrical or electromechanical in nature, but in more
recent times have become electronic in nature, relying
20 on microprocessors for controlling and carrying out
their functions. Moreover, while it was common at one
time for a residential security system to have external
controls (e.g., key-operated switches) to activate and
deactivate the system on exit and entry, which provided
25 a point of attack for potential intruders, it is more
common now for a microprocessor-based system to provide

09505695-034304
TOTAL 9999990

entry and exit delays, allowing all control interfaces to be within the protected perimeter of the premises.

As a result, the first place a returning occupant goes upon entering the residence is to the nearest control

5 interface for the security system, to disarm the system before expiration of the entry delay. Similarly, the last place a departing occupant goes upon leaving the premises is to the control interface, to arm the system.

10 [0004] Alternatively, or additionally, the user may have a transmitter, frequently provided in the form of a keyfob to be kept on the user's keyring, for arming and disarming the system. The transmitter may be a radio-frequency transmitter, in which case the user
15 would not necessarily have to be within close proximity to any particular location on the premises, or may be an infrared transmitter, in which case the user would have to be in close proximity to, or at least substantially in the line of sight of, a receiver,
20 which might conveniently be included as part of the control interface.

[0005] It also has become common for residences to be equipped with some sort of telephone answering device, which records a caller's incoming message,
25 name, and or telephone number, for playback or review by the resident upon returning home. The answering machine or caller identification device also is one of the first places to which a resident goes on returning home.

30 [0006] Most recently, it also has become common for individuals to have electronic mail accounts for receiving messages via the Internet or other public data networks. Thus, a third place to which a returning resident goes is to a computer, to retrieve
35 the electronic mail.

09805696 : 031304

[0008] The communications between the local security system and the remote central station has traditionally been carried by landline or cellular telephone or by radio. Frequently, more than one of those media are used, for redundancy. Increasingly, many of the protected premises, including both homes and businesses, have high-speed connections to the Internet. Using such connections to communicate to the central station would be faster than the other methods described above. However, there are several problems associated with using the Internet for central station communications.

[0010] Second, most Internet connections do not have
30 fixed Internet Protocol ("IP") addresses, meaning the
central station cannot be sure, simply from looking at
the originating address, that a message comes from a
particular location. Because the central station must
therefore accept messages from any IP address, and use
35 other data in the message to identify the sender, the

central station needs some other way to authenticate that the sender is who it appears to be.

[0011] Third, in most cases where the premises is served by an Internet connection, that connection is
5 protected by a "firewall" to prevent unauthorized access to computers on the premises -- e.g., by "hackers." This makes it difficult, if not impossible, for a central station to poll the security system on the premises via the Internet, because the firewall
10 prevents Internet access from the outside.

[0012] Fourth, the Internet has not yet reached a sufficiently mature state that it can be counted on to be available at all times. Service to a particular location may be "down" at unpredictable times.

[0013] Nevertheless, if a way could be found to use the Internet to communicate securely between a premises security system and a central station, and the system worked -- i.e., the connection was not "down," the Internet would clearly be the fastest communications
15 channel, as compared to landline or cellular telephone, or radio.

[0014] Such a system would have multiple channels available to get messages to the central station. It would be necessary to use those various channels in the
25 most efficient manner, avoiding unnecessary redundancy but also avoiding unnecessary delay in reporting to the central station.

[0015] It would be desirable to be able to minimize the number of electronic devices to which an individual
30 must attend on returning or leaving the premises.

[0016] It also would be desirable to be able to improve the security of communications between the premises and an external data network.

09030606 034304

Summary of the Invention

[0017] It is an object of this invention to minimize the number of electronic devices to which an individual must attend on returning or leaving home.

- 5 [0018] It is also an object of this invention to improve the security of communications between the home and an external data network.

[0019] In accordance with this invention, there is provided an integrated security and communications
10 system. The system has a security controller having at least one sensory input, at least one alarm output and at least one control signal input/output port. A control interface is operatively connected to the control inputs and outputs. A communications unit is
15 connected to a communication channel providing at least one communication function, and has a first communication port for connection to a control input and a control output of the security controller for providing at least one of its communication functions
20 to a user at the control interface.

[0020] In one embodiment of the invention, the communications unit is an electronic answering machine/voice-mail unit, providing an array of telephone answering and related functions. In another
25 embodiment, the communications unit is an Internet gateway. In a particularly preferred embodiment, the Internet gateway can communicate with the Internet securely from behind a firewall using shared private key encryption, creating a virtual private network.

30 Brief Description of the Drawings

[0021] The above and other objects and advantages of the invention will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which

09305696 "034304

like reference characters refer to like parts throughout, and in which:

[0022] FIG. 1 is a simplified schematic diagram of a preferred embodiment of a security system in accordance with the present invention;

[0023] FIG. 2 is a simplified schematic diagram of a second preferred embodiment of a security system in accordance with the present invention;

[0024] FIG. 3 is an elevational view of a first embodiment of a keypad for use in a system according to the invention;

[0025] FIG. 4 is an elevational view of a second embodiment of a keypad for use in a system according to the invention;

[0026] FIG. 5 is a simplified schematic diagram of the circuitry of the keypad of FIG. 4;

[0027] FIG. 6 is an elevational view of a third embodiment of a keypad for use in a system according to the invention;

[0028] FIG. 7 is a simplified schematic diagram of a preferred embodiment of a telephone interface unit according to the invention; and

[0029] FIG. 8 is a simplified schematic diagram of a preferred embodiment of a communications system according to the invention.

Detailed Description of the Invention

[0030] The present invention recognizes that the first place a user must go on entering a residence or other premises protected by a security system is to the security system keypad, to disarm the system (or place it in an "armed home" state) prior to the expiration of the entry delay period. The invention also recognizes that the last place a user goes before leaving the premises is to the security system keypad, to arm the system prior to leaving. In accordance with the

invention, communication functions, such as telephone answering or voice-mail functions, or Internet or other public data network functions, such as electronic mail, are made available to the user at the security system keypad. Depending on the number of functions provided, and the level of functionality provided for each function, it may be possible to use a conventional keypad, or an enhanced keypad may be required, as described in more detail below.

[0031] In order for the communications functions to be available at the keypad, the security system has to be integrated to at least some degree with the communications system or systems involved. While security systems ordinarily are connected to a telephone line -- e.g., for central station monitoring -- or to a radio-frequency or cellular communications device, greater integration than that normally provided is foreseen by the present invention.

[0032] In one preferred embodiment of the invention, an electronic answering machine or voice-mail unit is integrated into the security system and connected -- by wired or wireless connection -- to the household telephone line. If the household has a separate telephone line for security system monitoring, then the telephone line used for voice calls must be connected to the integrated voice-mail unit. In this system, the voice mail functions preferably are available at at least one, and preferably all, keypads of the security system.

[0033] In order to operate the voice mail functions, the security keypad preferably has at least eleven buttons, for the digits 0-9 plus one function key such as "#", and preferably a twelfth key such as "*", to mimic a standard DTMF telephone keypad. In addition, the keypad preferably has a speaker to play back any voice messages recorded by the system. Most

098055696-034304

conventional keypads already have a speaker for the purpose, e.g., of sounding a "pre-alarm" warning during the entry delay period (as a reminder that the system must be disarmed). It would also be desirable for the keypad to have a visual indicator that could be used for indicating the presence of messages to be played. However, this is not essential, as the system could be configured to announce aurally, on disarming of the system, whether or not there are messages, and if so how many. The user then uses keypad commands to play back the messages, delete them, archive them, etc. The system could also provide an audible indication on any connected telephone sets -- such as a repeating beep heard on top of the dial tone -- so that if a user picks up any such telephone set, it will be apparent that messages are present. The user could then use the telephone keypad to play the messages, etc.

[0034] It is known in voice-mail and telephone answering systems to provide multiple voice mailboxes, to which messages for different members of the household can be directed. It is also known to provide different security system user passcodes to different members of the household. In one embodiment of an integrated security and voice-mail system according to the invention, where individual voice mailboxes are provided, the entry of a particular passcode associated with a particular user, to perform any system function, also causes the system to play back, or at least announce the existence of, messages from that user's voice mailbox, or alternatively, from that user's voice mailbox and from a general mailbox, if there is one, but not from any other user's mailbox. In systems where users are provided, for control of the security functions, with swipe cards or transmitters that typically are coded differently for different individuals, then the use of such a card or transmitter

09805696-034304

or other coded token associated with a particular individual preferably has the same result as entry of an individual passcode. If the system has only one general mailbox, then any user's code would cause
5 playback, or announcement of the existence, of the general mailbox messages.

[0035] Another voice-mail function, commonly provided in stand-alone answering machines, that could be provided by the system according to the invention,
10 is the ability of one user to record a voice memo for another user. For example, a parent could record a reminder for a child to do his or her homework. When the child arrives at home and disarms the security system, the integrated voice-mail system would
15 recognize the child's passcode and play back, or announce the existence of, the voice memo, along with any voice messages in the child's mailbox.

[0036] The voice-mail functionality of the system is preferably provided by a telephone interface module
20 connected to the security system control unit and to the telephone line to be answered. Among other advantages, this allows the telephone interface module to be backed up by the security system back-up battery, preserving settings, recorded greetings, and recorded
25 incoming messages in the event of an AC power failure. Although known answering machines have battery back-up, integration with the security system means that the back-up battery is monitored by the central station, so that if it is low, a warning will be issued or a
30 technician sent to replace the battery, as discussed above. The system may be designed so that when it is operating on back-up power, it selectively sheds certain loads. For example, the system could turn off answering system functions or portions thereof such as
35 the digital signal processor whenever the system is on battery power, or only if the battery voltage drops

0980555-034304

[0037] The telephone interface module can be connected in parallel with the premises telephone wiring, but preferably is connected in series with the premises telephone wiring -- i.e., the incoming telephone line is connected to the telephone interface module, which in turn is connected to the premises telephone wiring. This would allow the voice-mail functions to be accessed from any telephone set on the premises, in addition to being accessed from the security system keypads. In addition, it would allow security system functions to be accessed from the telephone sets as well. Alternatively, in another embodiment, if the telephone interface module continually monitors the telephone line for DTMF activity, it could be connected in parallel with the premises telephone wiring and nevertheless allow the telephone sets to access either or both of voice-mail and security system functions. In still another embodiment, some of the telephone sets on the premises are connected to the telephone interface module while others are connected to the premises telephone wiring in parallel with the telephone interface module.

[0038] It should be noted that the integration of security system and telephone interface functions, such as the playback or announcement of the existence of voice messages upon disarming of the security system, requires that the passcodes for the security system and the telephone interface unit be the same. This is particularly the case if personalized mailboxes are provided, which is necessary if personalized recorded memos are to be provided, but is also necessary if the system is simply to record messages in a single mailbox and play them back. If the passcodes for the two systems are not the same, disarming of the security

5

10

15

20

25

30

35

[0040] Another feature that can be provided if at least some telephone lines on the premises are

5 connected to the telephone interface unit rather than
directly to the telephone provider central office, and
a personal computer on the premises is connected, via a
modem, to one such telephone line, is embodied in
software that can be provided on the personal computer.
10 The software causes the personal computer to send a
particular series of DTMF tones or other signalling to
the telephone interface unit, causing the telephone
interface unit to disconnect from the central office
telephone line and enter a programming/maintenance
15 mode. In this mode, the personal computer can be used
to inspect and reprogram settings of the telephone
interface unit. Preferably, this is done by
downloading a configuration file from the telephone
interface unit to the personal computer, changing the
20 configuration file, and uploading the new configuration
to the telephone interface unit. In addition, audio
files preferably can be transmitted between the
personal computer and the telephone interface unit,
allowing incoming voice mail messages to be downloaded
25 to the personal computer, and also allowing the user to
compose the outgoing message and other custom voice
prompts or tags on the personal computer and then
upload them to the telephone interface unit.

[0041] As in the case of many known telephone
30 answering or voice-mail systems, the voice-mail
functionality provided by the telephone interface
module according to the invention preferably is
remotely accessible by dialing into the system from an
external telephone. Moreover, because the telephone
35 interface module is connected to the security system
controller, then preferably security system functions

are accessible as well, whether dialing in from an external telephone, or picking up a premises telephone set.

[0042] Other functions offered by private-branch
5 exchange ("PBX") telephone systems could be offered to connected telephone sets by the system according to the invention. For example, memory dialing ("speed dialing") of some quantity of stored telephone numbers preferably is provided. In addition, in an alternative
10 embodiment in which the security system keypads are equipped with microphones, they could operate as additional telephone extensions, functioning as speakerphones. Even if the keypads do not have microphones, they could be used as extensions for
15 listening only -- e.g., to call recorded announcements or interactive voice-response systems.

[0043] Another function that the system preferably provides at either connected telephone sets, keypads or both, is call screening -- i.e., the ability to listen
20 to an incoming caller leaving a message, to be able to determine whether or not to pick up the call. Call screening is a common feature of stand-alone answering machines, but is less common in a PBX/voice-mail configuration. However, according to the invention, by
25 pressing an appropriate command, at a system keypad or on the keypad of a connected telephone set, while a message is being left, the message can be screened. And because a microphone is not needed for call screening, the screening function preferably is
30 provided even at a keypad without a microphone. Further, in accordance with the invention, a call being screened preferably can be answered by entering an appropriate command. This would have to be at a telephone set or, if provided, at a keypad with a
35 microphone. Preferably, the command to answer the call

090506034304

being screened, at least at a telephone set, is a flash of the telephone set hookswitch.

[0044] In a particularly preferred embodiment, the call screening feature is full-duplex -- i.e., the caller's voice can be heard over the system speakers even while the outgoing message or greeting is being played. Therefore, a caller who is aware of this feature, such as a member of the household, can announce him- or herself during the outgoing message in an attempt to cause a household member who may be at home to pick up the call. This differs from previously known answering machines -- whether digital or tape-based -- in that in those previously known machines, the caller's voice could be heard only after playback of the outgoing message was complete and recording of the incoming message had begun.

[0045] Another feature normally associated with telephone answering machines that can be provided in accordance with an embodiment of the present invention is the so-called "toll saver" feature. In accordance with such a feature, the answering system waits a first number of rings before answering an incoming call if no messages have already been recorded, but waits only a second, smaller number of rings if at least one message has already been recorded. This allows the residents, if they are away -- e.g., on vacation or holiday -- to determine when calling from a remote location whether or not there are any messages waiting, without necessarily completing a telephone call to the system. If the system rings more than the smaller number of rings, they know that there are no messages, allowing them to hang up the call before the system answers, and thereby saving long-distance toll charges. In a further embodiment, the "toll-saver" feature is selectable -- i.e., the user can control whether it is engaged at all -- and adjustable -- i.e., the number of

030506-034304

rings the system will wait before answering can be chosen by the user. User control of the "toll-saver" feature preferably is available at least at a system keypad, and preferably at connected telephone sets as well. More preferably, control of the "toll-saver" feature also is available when calling in to the system from a remote location.

[0046] In addition, operation of the "toll-saver" feature preferably can be programmed to be dependent on the state of the system, so that, e.g., it is inactive when the system is in a disarmed or armed-home state which means that the premises are occupied. This gives the residents or occupants more time to get to a telephone, or keypad if appropriate, when there is an incoming call and messages have been recorded.

[0047] Another feature that can be provided in accordance with an embodiment of the present invention is calling party identification, more commonly known as "Caller ID," in which the telephone carrier sends, with each incoming telephone call, calling party identification data which can be decoded and displayed by equipment at the receiving end. In an embodiment of the present invention, the telephone interface unit can include a calling party identification decoder, allowing the calling party identification data to be displayed at, in addition to the specialized Caller ID equipment, those keypads that have alphanumeric displays -- e.g., liquid crystal, gas plasma or light-emitting diode displays -- and on specially-equipped telephone sets connected to the telephone interface unit. In addition, using speech synthesis technology, the calling party identification data can be added to a recorded message left by a caller, for playback along with the message from any on-premises or off-premises location. Similarly, speech synthesis technology can be used to announce the calling party identification

0305096-034304

data aurally (e.g., over keypad speakers). In a further embodiment, the system can store textual identifying data -- e.g., names -- in association with certain telephone numbers, and can announce, either
5 visually, or aurally using speech synthesis, the name associated with a telephone number identified by the calling party identification data for each incoming call, either instead of or in addition to the number itself. Instead of using speech synthesis, the user
10 could store a "voice tag" recorded by the user -- e.g., "Mom's calling" -- in association with certain numbers, and the voice tag could be played back. In a still further embodiment, the system could store, in association with certain telephone numbers,
15 instructions for paging the user when a call is received from one of those numbers. When such a call is received, the system would dial the number of the pager stored in the instructions, and preferably may send, as a paging message, the calling number, most
20 preferably with some indication that the page is coming from the home system as opposed to directly from the calling number. Alternatively, the system could send as the paging message a message that one of the stored numbers has called, allowing the user to call home for
25 the voice mail message left by the caller.
[0048] Similarly, when "memory dialing" or "speed dialing" as discussed above is offered, the system could announce the number being called using speech synthesis, or could play back a stored voice tag stored
30 with the memory-dial number.
[0049] In another embodiment of the invention, the use of calling party identification technology also allows the provision of distinctive ringing -- i.e., a feature whereby calls from certain predetermined
35 telephone numbers ring differently from ordinary calls, to alert those on the premises that a particular party

09805596-034304

is calling. A number of different distinctive ringing patterns could be provided, each of which can be assigned to one particular predetermined number, or to a group of numbers. Thus, particular friends or
5 relatives could be assigned their own ringing signal, or a certain group of acquaintances -- e.g., all co-workers -- could be assigned a common ringing signal. [0050] While the distinctive ringing feature could be provided by including a ring generator in the
10 telephone interface unit, in a more particularly preferred embodiment, the distinctive ringing is provided by interrupting, in a predetermined manner, the incoming ringing signal provided by the telephone service provider. While this may limit the number of
15 different ringing signals that could be provided, it avoids the need to generate, within the telephone interface unit, a 90 VAC ringing signal as is commonly used in telephones.

[0051] In a further embodiment that relies on
20 calling party identification data, more than one outgoing greeting can be provided for each voice mailbox, with certain callers hearing a different greeting, as determined by the calling party identification data.

[0052] In another embodiment of the invention, the
25 telephone interface unit provides an auto-redial feature. When a user makes a telephone call, if the called number is busy, the telephone interface unit will continue to call the called number at
30 predetermined intervals until it detects a ringing signal. When a ringing signal is detected, an indication is made at the user premises, either by ringing the telephones, providing a visual indication on a telephone equipped with a visual indicator, or
35 providing an aural or visual indication at a one or more system keypads, or any combination. If a user

TOP SECRET

does not pick up a telephone within a predetermined interval after the indication is made, the system will disconnect the call. The user has the option of terminating the redial feature, which in any event is preferably limited in duration after the initial busy signal is detected -- e.g., the system may attempt to redial the call every two minutes but only for half an hour after the initial busy signal.

[0053] Another feature that is provided in a preferred embodiment of the invention is a public address feature. A user can pick up a telephone set connected to the telephone interface unit and, by issuing an appropriate command, either on the telephone keypad or on a specially-provided button, disconnect the telephone set from the central office line and connect it to the speakers in the system keypads for broadcast of an announcement. Alternatively, individual keypads, or groups of keypads, could be addressed by telephone keypad commands. In a variant of this feature, another user, on hearing the announcement, can pick up another telephone set and, upon entering an appropriate command, be connected to the first user in an "intercom" mode, disconnected from the central office telephone line. The intercom or public address mode preferably is also available when the telephone line is in use. Specifically, if a user answers an incoming call, but the call is for another user on the premises, the user who answered the call could engage the public address or intercom function to advise the user for whom the call is intended. In such a case, while the telephone sets would be temporarily disconnected from the central office telephone line, the telephone interface unit would maintain the telephone line in an off-hook condition (i.e., "on hold") until one of the users is ready to pick up the call. Of course, these features would not be available

09605696-034304

from a telephone set that is connected to the central office telephone line directly rather than through the telephone interface unit.

- [0054] In addition to providing a public address
- 5 function, the telephone interface unit could also provide a room-monitoring function. Specifically, the system would allow a user to issue a command on any connected telephone set to monitor the microphone of any microphone-equipped keypad on the system.
- 10 Preferably, the appropriate command could also be issued from any other keypad, as long as the other keypad has a speaker for listening, whether or not it has a microphone. This feature could be used, for example, to monitor a baby's room.
- 15 [0055] In another alternative embodiment of the invention, instead of providing voice-mail functionality in the telephone interface unit, the user could subscribe to central office voice-mail service from the telephone company. Normally, a subscriber to
- 20 that service is informed of waiting messages by a special dial tone that is audible only when a telephone set is picked up. In this embodiment of the invention, the telephone interface unit senses the presence of the special dial tone and causes an aural or visual
- 25 indication at one or more system keypads, and, in a further alternative, visually on specially equipped telephone sets connected to the telephone interface unit. In addition, the system could, upon command from a keypad, connected telephone set, or other connected
- 30 communications device, or upon disarming of the security system, dial out on the central office telephone line the DTMF digits, including the user's access code, necessary to accessing the voice mail service (or other functions) provided by the central
- 35 office, playing back the messages at the device from which the command was entered.

FOUO 9690360

[0057] Many of the features described above are provided by having the telephone interface unit monitor incoming telephone calls on connected telephone sets and even on unconnected telephone sets. That same monitoring capability can be used to monitor outgoing telephone calls, and in accordance with another feature of the invention, the system can keep a log of outgoing calls including such information as number called, time of call, duration of call, etc. This information preferably can be displayed on the display of a telephone set so equipped or on the display of a security keypad so equipped. Moreover, the system could then be used to block certain telephone calls, such as those to "900" numbers, or to specific numbers programmed into the system, or even long distance calls. As a further feature, such calls could be unblocked by entering an appropriate code. Of course, to use these blocking features, the telephone sets would have to be connected through the telephone interface unit; telephone sets connected directly to the central office line in parallel with the telephone interface unit would have unlimited access to the telephone line. Thus, a user interested in these features typically would not have any telephone sets that are not connected through the telephone interface unit.

[0058] In addition to, or instead of, being connected to a telephone line, the security system according to the present invention can be connected to an external data network for sending or receiving data.

5 One example of such a network to which the system can be connected is the Internet. Preferably, if the system is connected to an external data network such as the Internet, the connection is of the type which is always on and active. The external data network may

10 used as a backup channel for communication with the central station that monitors the security system, with a traditional dial-up or cellular telephone connection or radio-frequency communication channel as the primary channel, but the external data network also could be

15 used as the primary central station monitoring channel, with the traditional communications methods used as back-up. Either way, preferably the various channels are used redundantly to make sure that the message gets to the central station. More preferably, once

20 transmission on one channel succeeds, incomplete attempts using other channels are terminated, as described in more detail below.

[0059] In accordance with another aspect of the present invention, an Internet connection between the

25 premises and the central station can be used for reliable secure communications. Both of the problems of security and authentication are solved by using shared private key encryption. Each premises system is provided with a unique private key. For example, in a

30 preferred embodiment, the private key is built into the system controller at the time of manufacture. The same private key is shared with the central station. The central station thus stores many private keys, one for each of the units it monitors. If the central station

35 is communicating with a particular unit, if it is able to decrypt the communication with that unit using the

0930336-034304

private key that it associates with that unit, which no one else in the world is supposed to know, then the central station knows two things. First, the central station knows that the unit is the unit that the

5 central station thinks it is, because if it were a different unit, the private key would not function to decrypt the communication. Second, by virtue of the same private key encryption, the central station knows that the communication was secure.

10 [0060] The remaining problem of the premises firewall is solved by having the premises unit initiate contact with the central station periodically. Most firewalls do not prevent sessions that initiate within the firewall. Once a session is open, the central

15 station can send any messages or other data to the premises unit. If the central station does not hear from the premises unit at the appointed intervals, it assumes a problem and dispatches someone to the premises. Otherwise, the contact intervals are set to

20 be short enough that the central station is not likely to have too much of a build-up of unsent messages to the premises. The contact interval may also depend on the type of premises. For example, a bank or jewelry store may have more frequent contact with the central

25 station than a residence.

[0061] Although the system is useful to allow communications through firewalls, it may be used where one or both of the communicating parties lacks a firewall. Advantages of such a system include

30 obviating the need for user setup, as well as the need for an external data center to know the IP address of a device with which it needs to communicate.

[0062] Although in the system just described, the installation in secure contact with the premises has

35 been described as a "central station," it need not be the same "central station" that monitors for and

098036-03301

responds to alarm conditions. Instead, it is possible to distinguish between a central monitoring station, which performs those traditional alarm monitoring functions, and a central communications station, which
5 merely guarantees the security of the communications link. While in some cases, both of those functions may in fact be performed by a single entity, it is within the present invention for those functions to be performed by separate facilities which may even be
10 owned by separate entities. Thus, while traditional alarm companies will continue to operate central monitoring stations, they may contract with secure communications providers to operate central communications stations to provide secure Internet
15 connections to their subscribers and then to relay the communications to them.

[0063] Indeed, that relay may take place over an Internet connection between the central monitoring station and the central communications station that is
20 secured in the same way as the connection between the subscriber premises and the central monitoring station. Specifically, the central monitoring station, secure behind its firewall, will initiate all sessions with the central communications station using a shared
25 private key encryption.

[0064] If the central monitoring station in such an embodiment wants to contact a subscriber premises unit, the central monitoring station initiates a session with the central communications station and transmits the
30 message to the central communications station. The central communications station queues the message for the appropriate premises unit, and when that premises unit next checks in, the central communications station asks the premises unit to hold the channel open to
35 receive the message from the central monitoring station. The central communications station then sends

09803696-034304

5 transmitted to the central monitoring station.

10 station. The central communications station queues the
message until the central monitoring station next
checks in, when the central communications station asks
the central monitoring station to hold the channel open
to receive the message from the premises unit. The
15 central communications station then sends the message
to the central monitoring station, and receives a
response, if appropriate. If a response is received,
it is queued up until the next time the premises unit
checks in, at which time it is transmitted to the
20 premises unit.

20 premises unit.

25 available. If it is not available, one or more of the
other communications channels can be used.

30 invention, the system does not wait for failure of the
primary channel before initiating contact on a
secondary channel:

35 would be to have both (or all if more than two channels
are used -- e.g., Internet, landline telephone,

cellular telephone, control-channel cellular communications such as that known as MicroBurst[®] and available from Aeris Communications, Inc. of San Jose California, and/or radio) channels initiate

5 communications at the same time, with the first method to succeed issuing instructions upon success for the other methods to terminate their attempts to communicate. This scheme has the advantage that the reporting of an alarm condition (or any other

10 condition) need not wait until the primary channel fails before a secondary channel is tried.

[0068] On the other hand, the primary channel frequently works. Therefore, the dynamic signalling scheme just described could be considered inefficient

15 in that it always initiates the back-up channel(s) even when no back-up is necessary. Therefore, in a refinement of the dynamic signalling scheme, the primary channel is given a "head start" before the secondary channel or channels are activated. For

20 example, if the primary channel is the Internet, then a successful reporting session normally will be over in a few seconds. Therefore, the other channels automatically are engaged after, e.g., five seconds, unless a completion signal is received from the primary

25 channel. If the primary channel is successful within five seconds, then there is no need to activate the other channels at all. If the primary channel is not successful within five seconds, it may yet be successful, but the other channels will be activated,

30 with the first channel to succeed after that time terminating the other channels.

[0069] Various combinations of channels can be used. For example, the system could rely on control-channel cellular communications or the Internet as the primary

35 channel, with landline dial-up as the backup channel. Or the Internet could be the primary channel, with

0950696-034304

control-channel cellular communications as the backup the channel. Any other combination of the various communications media could be used.

[0070] Once the external data network is present,
5 other uses beyond security system reporting are possible. Thus, a properly equipped premises system keypad could be used as a terminal for accessing the external data network. In one preferred embodiment, when a user disarms the security system at a system
10 keypad -- e.g., on returning home -- incoming electronic mail messages are displayed at the keypad. For this purpose, the system keypad preferably has an alphanumeric display, or an active-matrix, LCD or other flat-panel display, to display the electronic mail
15 messages, although speech synthesis technology could be used to present the messages aurally using a speaker in the keypad. Preferably also, the keypad has a visual indicator to indicate the presence of messages to be displayed. An aural indication -- such as a particular
20 pattern of tones or a recorded or synthesized spoken announcement -- of the presence of messages could be provided at the time of disarming the system, instead of, or in addition to, a visual indication.

[0071] If electronic mail is delivered by the
25 system, then in one embodiment there is a particular electronic mail address associated with the system, and that mail would be displayed. In a more particularly preferred embodiment, a separate electronic mail address for each authorized user of the system is
30 associated with the system, and the appropriate user's electronic mail messages are displayed based on the passcode, swipe card, coded transmitter or other token used to disarm the system, as discussed above in connection with telephone voice-mail messages. Thus,
35 the announcement and/or display of electronic mail messages via the keypad is personalized to the user who

09805696 "034304
T02T20" 96950850

is within the vicinity of, or is accessing, the keypad. Such personalization significantly enhances the usability and "user-friendliness" of the system.

[0072] In another embodiment of the invention,
5 instead of, or in addition to, electronic mail messages, the system displays World Wide Web pages or similar data from the external data network. The data displayed are preselected by the user or users. Thus, the same data could be accessed regardless of who
10 accesses the system, or the data could be personalized for individual users. For example, in a residential system, if an adult disarms the system, a stock market report might be displayed, while for a teenage child, an advertisement from a favorite retailer might be
15 displayed. Similarly, on arming of the system, which ordinarily signifies that the user is leaving the premises, a traffic or weather report, or any other data preselected by the user, might be displayed. If a user has more than one passcode, or a transmitter with
20 more than one button for arming or disarming the system, a different data selection could be associated with each passcode or button.

[0073] In another embodiment, the system is configured to allow retrieval of electronic mail
25 messages from any one or more system keypads throughout the premises, separately from a disarm operation. This could be implemented in one embodiment by providing a special electronic mail retrieval key on the keypad, which would then prompt the user for a passcode to
30 identify which of the potential authorized users is requesting retrieval of electronic mail, or in a second embodiment a special command sequence on a standard keypad could be used for the same function. In another embodiment, the various system keypads on the system
35 could be configured in a local area network, allowing users at different keypads to independently and

09805536-034304

simultaneously retrieve electronic mail. In such an embodiment, the security system functions operate as in the non-networked embodiment.

[0074] In a further embodiment, the system keypad is
5 provided with a full keyboard and is usable as a terminal to log onto the Internet or other external data network for any purpose, including composing and sending electronic mail, searching for information on the World Wide Web, etc. In a variation of this
10 embodiment, the keypad is provided with a microphone for full sound operations, and optionally with stereo speakers instead of a single monaural speaker. In another variation, the keypad is also provided with a display, such as a liquid crystal or gas plasma display
15 or a small cathode-ray tube display, for displaying graphics as well as text, and optionally with a video camera for full video operations.

[0075] The premises unit could perform all of these functions on its own, using its direct external data
20 network (e.g., Internet) connection. However, for security reasons, it may be desirable to avoid general contact between the premises unit and other Internet users. Therefore, in a system where the premises unit communicates with a central communications station as
25 described above (whether or not the central communications station is also the central monitoring station), the central communications station could maintain, by user subscription, records of user e-mail addresses and content preferences (i.e., what news,
30 weather, advertising, etc., the user wishes to receive, and when), retrieve the data from the Internet (e.g., using appropriate "agents") and send it to the premises unit based on received passcodes. If direct interactive Internet use is available on the system
35 (which may depend, primarily, on how good the keyboard is on the user interface), the central communications

09805696 034304

[0076] According to another feature of the invention, a user's passcode unlocks other passwords that the user may have with other institutions, such as banks or other financial institutions. In one embodiment, the passwords are stored in the premises controller. Based on the entry of a user's passcode to access the system, if the user then initiates a session with one of those institutions, the appropriate password is transmitted, when needed, to the institution without further action by the user.

[0077] In another embodiment, the user's security system passcode is registered with the institutions as a secure identifier of the user. When the user accesses the premises system with his or her passcode or coded token and then uses the external data network to log into the financial institution, the passcode is sent to the institution and is recognized as a secure authorization. While this function would have to be by agreement and prior arrangement with the financial institution, it is potentially more secure, or at least less risky, than sending a personal identification number ("PIN") over the external data network, even in encrypted form.

[0078] In a particularly preferred embodiment, the passwords are stored at the central communications station. If the user wants to perform, e.g., a banking transaction, the users accesses a software banking agent at the central communications station and specifies the transaction, but need not enter his or

5
.
10

15

20

25

30

35

[0081] Access to the premises system from the external data network preferably also is through the central communications station. For example, the central communications station could maintain a World Wide Web site through which subscribers could contact their home systems from elsewhere. Thus, a subscriber at his or her place of employment could log onto that web site and issue a command to turn on a certain appliance in the home. The systems at the central communications station, after being satisfied that the user is authorized, would queue up those instructions until the next time the home system makes contact, at which time the instructions would be sent, and the appliance would be turned on.

[0082] The invention will now be described with reference to FIGS. 1-7.

[0083] A preferred embodiment of a premises security system 10 according to the present invention is shown in FIG. 1. A system controller 11, similar to a Model 6139T available from the Alarm Device Manufacturing Company ("Ademco," a division of Pittway Corporation), of Syosset, New York, is modified to communicate over a bus 12, preferably a four-wire bus, with at least one communications interface 13. Communications interface 13 can be a telephone answering/voice-mail/PBX type interface as described above. Alternatively, communications interface 13 can be an external data network/Internet interface, also as described above, which may be a router or ADSL (asymmetric digital subscriber loop) interface, providing continual access to the Internet over external communications line 14 which may be a suitable persistent Internet connection. Communications interface 13 also could be a modem, preferably a 56 kbps modem, providing a dial-up connection over external communications line 14, which could be a standard analog telephone line.

0980566-034304

Controller 11 preferably has a back-up battery 113 serving at least both controller 11 and communications interface 13.

[0084] System 10 also includes conventional
5 sensors 15, which may include security or fire sensors or both, and one or more conventional or enhanced system keypads 16 as discussed above and as described in more detail below. Keypads 16 may be connected directly to controller 11 in the conventional manner,
10 as shown, in which case the communications functions are routed between keypads 11 and communications interface 13 through controller 11. Alternatively, keypads 16 may be connected to bus 12 for routing of both security system signals to and from controller 11
15 and communications functions to and from communications interface 13. In yet another alternative, keypads 16 can be connected both directly to controller 11 (for security functions) and to bus 12 (for communications functions). Controller 11 preferably is connected to a
20 sounder 110 (e.g., a bell or siren) for sounding alarm conditions, and preferably is connected to a dialer unit 111 for communicating with a central monitoring station over, e.g., a standard telephone line.

[0085] One or more communications devices 17 could
25 be connected to communications interface 13, either by a direct connection or through bus 12 as shown (but ordinarily not through both connections).

Communications devices 17 could be telephone sets if communications interface 13 is a telephone system
30 interface as described above, or could be personal computers or computer terminals if communications interface 13 is a data network interface as described above.

[0086] If communications interface 13 is a telephone
35 system interface, telephone sets 17 preferably would be connected directly to communications interface 13,

0980596-034304
T02E0-9694860

although additional telephone sets could be connected directly to the central office telephone line (see FIG. 2). Communications devices 17 could also include a modem connected to a personal computer, allowing the personal computer to be used to access the communications interface 13 in the manner described above, for programming features of communications interface 13, or for downloading and storing incoming voice mail messages from communications interface 13.

10 [0087] If communications interface 13 is a data network interface, personal computers or computer terminals 17 preferably are connected to communications interface 13 via bus 12, although a direct connection (e.g., a local area network Ethernet connection) can also be used.

15 [0088] FIG. 2 shows another preferred embodiment of a system 20 in accordance with the invention. System 20 is similar to system 10, except that a separate telephone interface unit 21 and a separate data interface unit 22 are shown. It should be clear, however, that the system according to the invention could include only one or the other of interfaces 21, 22.

20 [0089] As shown, in system 20, sensors 15, keypads 16, sounder 110 and dialer 111 are connected to controller 11 as in system 10 of FIG. 1. Telephone interface unit 21, which preferably is connected to standard analog telephone line 23, preferably is connected to controller 11 by bus 12. A first group of telephone sets 24 preferably is connected to telephone interface unit 21. The telephone answering/voice-mail/PBX functions described above preferably are available at keypads 16 either via bus 12, or through controller 11 to which keypads 16 may be directly connected. The telephone answering/voice-mail/PBX functions described above may also be available to

25
30
35

0980596-03304

those telephone sets 24 connected to telephone line 23 through telephone interface unit 21. Another group of one or more telephone sets 25 may be connected directly to telephone line 23. In one embodiment of the invention, the telephone answering/voice-mail/PBX functions described above would not be available at telephone sets 25. However, in an alternative embodiment of the invention, telephone interface unit 21 could monitor telephone line 23 for DTMF tones signifying certain command signals, and provide the corresponding functions even to telephone sets 25. However, telephone interface unit 25 would be unable to disconnect any one of telephone sets 25 from telephone line 23, and therefore could not perform any function that required such a disconnect, such as the public address function over keypad speakers. A limited number of functions, where the dialing of the commands would not cause a telephone call to be placed, might be available.

[0090] Data interface unit 22, which preferably is connected to data line 26, preferably is connected to controller 11 by bus 12. Optionally, one or more personal computers or computer terminals 27 preferably is connected to data interface unit 22 -- e.g., by a local area network (shown as a direct link to data interface unit 22) -- for the purpose of sharing data line 26. The data functions described above preferably are available at keypads 16 either via bus 12, or through controller 11 to which keypads 16 may be directly connected. The data functions described above may also be available to those personal computers or computer terminals 27 connected to data interface unit 22. Alternatively, personal computers or computer terminals 27 could simply share data line 26 by an alternate connection shown in broken line, without being connected to data interface unit 22.

090506 "034304
F0220" 9290860

5

10

15

25

30

35

perform standard security system indications -- e.g., a warning that a zone is bypassed, an indication that the system has been in alarm, an AC power failure, etc. -- as well as telephone interface indications such as a message waiting indication. Alphanumeric display 34, which may be a standard two-line, sixteen character per line, display, also provides security system indications, and telephone interface indications such as, e.g., calling party identification data.

10 [0095] Keypad 30 preferably also has a speaker 35, as is conventional for providing, e.g., a pre-alarm aural indication, which may also be used to provide aural telephone interface indications such as an aural message waiting indication, and more particularly may be used for the playback of messages. Speaker 35 could also be used to allow a user to make telephone calls (using keys 31) to announcement-only or voice-response telephone numbers where two-way communication is not necessary. In an alternative embodiment, keypad 30 includes a microphone, allowing the recording of outgoing voice-mail greetings. If the system is configured, as just discussed, to allow telephone calls to be placed from keypad 30, microphone 36 could be used to make such calls.

20 [0096] FIG. 4 shows an embodiment of a preferred embodiment of an enhanced keypad 40 designed to work with data interface unit 22 to perform data functions. Thus, keypad 40 preferably has, instead of numeric keypad 13, a full alphanumeric keypad 41, along with function buttons 32 and visual indicators 33. Keypad 40 preferably also has a full graphic display 44 in place of alphanumeric display 34. Display 44 could be a liquid crystal display ("LCD"), gas plasma display or cathode-ray tube ("CRT"), which could be a color or monochromatic display. Display 44 could further provide touch screen capability, in which case

095050504

alphanumeric keypad 41 could be a "soft" keypad that can be called up on display 44 when desired.

Preferably, keypad 40 also has two speakers 45, for stereo audio functions, if necessary, although in an
5 alternative preferred embodiment only one speaker 45 may be provided. Keypad 40 preferably also has a microphone 46, and optionally has a video camera 47 for full-duplex video functions, if necessary.

[0097] A schematic block diagram of circuitry 50 of
10 a keypad similar to keypad 40, but incorporating some of the functions of data interface unit 22, is shown in FIG. 5. If multiple such keypads are provided, the additional "slave" keypads may omit the data interface circuitry, or may include it even though it may be
15 redundant. Circuitry 50 preferably is built around a central processing unit ("CPU") 51 such as an 80386 or equivalent microprocessor, available from Intel Corporation, of Santa Clara, California. Preferably connected to CPU 51 is random-access memory ("RAM") 52
20 as well as non-volatile memory 53 (e.g., NVRAM). If the system uses shared private key encryption as discussed above, the private key preferably is stored in non-volatile memory 53. An audio interface 54 preferably also is provided, interfacing with external
25 data network 26 for audio input/output functions, as well as interfacing with audio signals from telephone interface unit 21, if present in the system.

[0098] Expansion bus 55 preferably connects CPU 51 to keypad 41 and indicators 33. Expansion bus 55 also
30 preferably connects to a network interface 56 which allows several keypads 50 to be attached to system 20 for operation of the security functions of controller 11, for independent access to external data network 26, and for connection to other keypads 50 in a
35 local area network on the premises served by system 20. A graphics controller 57, preferably having its own

095036-03304

associated graphics RAM 570, preferably is also connected to bus 55 allowing CPU 51 to drive graphical LCD display 44. A touch screen interface 58 connected to CPU 51 preferably is integrated (not shown) with display 44.

[0099] A real-time clock 59 preferably is provided for CPU 51, and the entire circuitry 50 preferably is powered by a 12-volt DC power supply 500 as indicated by dashed lines 501.

[0100] Finally, interface 502 connects to controller 11, preferably via bus 12, while connection to external data network 26 preferably is provided by serial interface 503 which is, or connects to, a router, ADSL interface, modem or other data connection device.

[0101] A preferred embodiment 400 of a simplified keypad for use with the invention is shown in FIG. 6. Keypad 400 preferably includes a subset of the features of keypad 40. Thus, it preferably includes a full graphic display 44 with touch screen capability, avoiding a full alphanumeric keypad 41, but allowing for a "soft" keypad that can be called up on display 44 when desired. Preferably, keypad 400 also has one speaker 45 and a microphone 46.

[0102] A schematic block diagram of circuitry 60 of a preferred embodiment of a telephone interface unit 21 according to the invention is shown in FIG. 7. A central processing unit (CPU) 61 preferably controls the various telephone interface and voice-mail/telephone answering functions described above, as is conventional. Digital signal processor (DSP) 62, connected to CPU 61, handles the voice processing functions required for the voice-mail/telephone answering functions. As discussed above, DSP 62 preferably allows full-duplex operation, so that if an incoming call is not picked up on one of the premises

09505596-034304

5

10

15

30

35

set is intended as a security system command or a PBX/
voice mail/answering machine command, or conversely
whether a signal or command from security system 11 or
CPU 61/DSP 62 is intended as a telephone-related
5 command or a security system command. This allows
commands to be routed properly, and also allows devices
to be taken on-line or off-line as appropriate (e.g.,
to disconnect telephone sets from the central office
phone line when a telephone set is being used to
10 broadcast a message over the keypad speakers).

[0105] A modem 601, as may be conventional, may be
connected to telephone line interface 602 for purposes
described above. In addition, modem 601 could serve as
a back-up security communications device, allowing
15 controller 11 to communicate with a central monitoring
station if normal channels are unavailable.

[0106] Telephone line interface 602 is also
connected via CODEC 65 to CPU 61 and DSP 62 to allow
CPU 61 and DSP 62 to perform the PBX/voice mail/
20 telephone answering functions described above.

CODEC 66 connects DSP 62 to security system audio
bus 603 (also connected to security system
interface 600), allowing circuitry 60 to communicate
with security system keypad speakers. In addition,
25 telephone line interface 602 connects the central
office telephone line and the premises telephone sets
to the system and to each other. Those connections
preferably are made through suitable relays (not shown)
so that in the event of a power failure, the central
30 office telephone line would be connected directly to
the premises telephone sets, maintaining telephone
service on the premises.

[0107] The entire circuitry 60 preferably is powered
by a nominal 12-volt DC power supply from security
35 system controller 11, as indicated by dashed lines 604.

09050360

[0109] Each premises system 703 preferably includes a system 10 as shown in FIG. 1, preferably including an interface unit 50 as shown in FIG. 5 storing a private key. System 10 within system 703 has an Internet
15 access unit 705, with access controlled by firewall 706.

25 [0111] Central communications station 701, in
addition to having an Internet access unit 705 and a
firewall 706, has remote application servers 708 (these
may be located elsewhere at the premises of the
providers of the services on servers 708). Central
30 communications station 701 also includes secure
redirectors 711 which have access to private key
storage 709 to store the private keys of all of the
systems with which it communicates. Redirectors 711
perform the encryption and decryption using those keys
35 to communicate with those systems.

[0112] Central communications station 701 communicates with the Internet 704 through firewall 706 and Internet access unit 705, connecting the Internet to insecure bus 713. Communications on insecure bus 713 that are destined for remote servers 708 pass through redirectors 711 to secure bus 714, with security based on the private keys stored at 709.

[0113] Another web server 712 maintains the web site described above that allow users from any Internet access location 710 to issue instructions to premises systems 10. Because the point of web server 712 is to allow a user at any Internet access point 710 to access his or her secure system 703, and access point 710 likely is not registered to use redirectors 711, web server 712 preferably is protected, as shown, by conventional security such as SSL (secure socket layer) encryption, smart cards, etc.

[0114] Among remote servers 708 are relay servers to relay communications between the various systems 702, 703, as well as from server 712 to units 50 of premises systems 10 in units 702, as described above, after secure channels are opened by secure redirector units 711.

[0115] Central communications station 701 may be separate from central monitoring station 702 as shown, or stations 701 and 702 could be combined or co-located. Similarly, regardless of their relative locations, they could be operated by the same or different parties.

[0116] The communications system as described could be used to offer or implement a number of security features.

[0117] One function of central alarm monitoring systems is to "supervise" high-security premises systems such as a bank alarm system. Traditionally, a poll-and-response system was used in which the central

0950550-03404

station contacted each supervised system individually on a periodic basis to make sure it received a response, and to check the system's status. If it did not, or if its status was not normal, appropriate
5 action was taken. In later systems, the supervised system simply called in periodically on its own, without the need for polling. Again, appropriate action was taken if the supervised system did not check in on time, or its status was not normal. In
10 accordance with the current invention, because the premises system has to check in periodically, it can be programmed to report its status at the same time. The system's failure to check in, or to report a normal status, is acted upon appropriately.

15 [0118] Similarly, two premises systems 10 can be made to operate as a single system by communicating through central communications station 701. For example, if a company has multiple locations, passcodes for individual employees can be entered only in the
20 system at their "home" location, but the systems at other locations would recognize those passcodes because the systems could communicate through central communications station 701. Although such systems can be implemented by running wires between adjacent
25 buildings, the present invention allows such systems to be implemented between far-flung locations without running wires or leasing expensive dedicated lines.

[0119] Another function that could be implemented using the present invention is the download of
30 configuration data to system 10. Configuration data for user interface 16 or 50, including web site preferences for various users, etc., as well a security configuration data for controllers 11, could be stored at a remote server 708 and downloaded when its
35 particular system checks in to see if any other system wants to contact it. In the case of downloading of the

09000000-00000000

configuration of security controller 11, this eliminates the need for central alarm station operators to maintain separate dialer banks for downloading as they do now.

5 [0120] In accordance with another function of the present invention, if one of home automation devices 215 is a video camera, the system allows a user at any terminal 710 on the Internet to securely access that video feed. The user logs onto web server 712 and
10 requests the video feed. The next time the system 703 of which the desired video camera is a part checks in, redirector 711 established a link to server 712, which relays the video feed to the user. In an alternative to this embodiment, which consumes a lot of bandwidth
15 because of the nature of video, the system can avoid relaying the video, and thereby conserve bandwidth, by enabling secure direct communications between terminal 710 and system 703. This can be done by, after authenticating both parties, sending to each
20 party a session key (generated, e.g., by secure session key generator 715) and the IP address of the other party, and allowing the parties to communicate directly. Each party knows that it received the session key and the other party's address securely, and
25 therefore when they establish communications with each other, they are confident that the communication is authorized. In fact, such an arrangement can be used even for low-bandwidth communications if desired.

[0121] Although each of the components of
30 communications system 700 as shown includes a firewall 706, firewall 706 could be omitted from one or more components. As discussed above, the system has advantages even without firewalls.

[0122] In another embodiment system 10 need not
35 include any security features at all. Instead, system 10 could include only communications features,

09805696-034304

[0123] Preferably, in an embodiment including security features, each system 10 includes at least one secondary communications channel, illustrated in FIG. 7 as dialer 712, which preferably is connected to telephone interface 713 of monitoring station 702 by public switched telephone line 714. Of course, the secondary channel may instead, or also, include one or more alternate channels such as a cellular telephone, control-channel cellular, or a radio link (not shown). As discussed above, the system could try both (or all) channels, with the first channel to succeed issuing a signal or command through system 10 to terminate the other channel(s). However, also as discussed above, preferably the primary channel is started ahead of (e.g., five seconds ahead of) the secondary channel(s). The secondary channels are initiated only if the primary channel is not successful within the "head start" period. After that, all of the channels attempt to communicate with monitoring station 702 and the first to succeed, which may still be the primary

[0123] Preferably, in an embodiment including security features, each system 10 includes at least one secondary communications channel, illustrated in FIG. 7 as dialer 712, which preferably is connected to telephone interface 713 of monitoring station 702 by public switched telephone line 714. Of course, the secondary channel may instead, or also, include one or more alternate channels such as a cellular telephone, control-channel cellular, or a radio link (not shown). As discussed above, the system could try both (or all) channels, with the first channel to succeed issuing a signal or command through system 10 to terminate the other channel(s). However, also as discussed above, preferably the primary channel is started ahead of (e.g., five seconds ahead of) the secondary channel(s). The secondary channels are initiated only if the primary channel is not successful within the "head start" period. After that, all of the channels attempt to communicate with monitoring station 702 and the first to succeed, which may still be the primary

channel (e.g., if the Internet is the primary channel, there may have been a delay caused by heavy traffic), will upon success terminate the other channels by issuing a signal or command through system 10.

5 [0124] The primary channel, which is given the head start, is preferably the fastest channel, because if it works, it normally will work fast enough to avoid having to activate the other channels. In a system where the Internet is available as a channel, it would
10 be the fastest channel. Control-channel cellular would be the next fastest and would be given the head start in a system without Internet access. Radio would be the next fastest and would be given the head start in a system without Internet access or control-channel
15 cellular. Cellular and landline telephones have comparable speeds; if they are the only available channels, the landline telephone is normally tried first and given the head start.

[0125] A user of the system according to the
20 invention preferably can access telephone and data functions at one central location on entering the premises. Thus it is seen that a security system is provided that minimizes the number of electronic devices to which an individual must attend on returning
25 home, by combining the functions of several of those devices. The system can also be used at any time that the user is at home. Secure communications between the premises system and other systems is also provided. One skilled in the art will appreciate that the present
30 invention can be practiced by other than the described embodiments, which are presented for purposes of illustration and not of limitation, and the present invention is limited only by the claims that follow.

09805696-034304